

View Online at <https://aerobasegroup.com/nsn/3110-00-235-2414>

Shank Diameter:

Between 0.6230 inches and 0.6250 inches

Shank Style:

Hollow

Overall Length:

2.7190 inches

Bore Diameter:

Between 0.2498 inches and 0.2500 inches

Overall Outside Diameter:

0.9380 inches

Lubrication Material:

Grease

Outer Ring Width:

0.4380 inches

Inner Ring Width:

Between 0.5880 inches and 0.5930 inches

Length From Bore Center To Shank End:

2.2500 inches

Shank Bore Diameter:

Between 0.5000 inches and 0.5150 inches

Shank Bore Depth:

0.8750 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Self-alignment Angle:

10.00 degrees

Special Features:

0.0004 in. Maximum radial clearance, starting torque 0.052 inch lbs max, shank void filled with narmco 3119 putty, 0.015 in. By 45 degrees chamfer on od of shank

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel rod end body

Style Designator:

Double row, staggered, ball

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.