## NSN 3110-00-249-5222

Needle Bearing Cam Follower - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-00-249-5222 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.0460 inches and 0.4680 inches **Overall Length:** 1.1093 inches **Overall Outside Diameter:** Between 0.7490 inches and 0.7510 inches **Lubrication Material:** Grease Stud Diameter: Between 0.3110 inches and 0.3120 inches **Outer Ring Width:** Between 0.3390 inches and 0.3440 inches Stud Length: Between 0.7190 inches and 0.7810 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.312 inches **Special Features:** Extended portion of stud heat treated rc 36-4, 0.076 diameter hole in thd end located 0.109 in. From end, magnectic particle insp, internal diametral looseness 0.003 to 0.0013 in. Ma, nas-516-1 alemite fitting in flange end of stud **Lubrication Material Specification:** Mil-g-23827 military specification single material response Material: Steel end plate **Surface Treatment:** Cadmium all external/exposed metal surfaces **Surface Treatment Specification:** Qq-p-416 type 1 class 2 federal specification 2nd treatment response all external/exposed metal surfaces **Style Designator:** Cam follower **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

No

Demilitarization:

## NSN 3110-00-249-5222

Needle Bearing Cam Follower - Page 2 of 2



Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.