

View Online at <https://aerobasegroup.com/nsn/3110-00-277-0171>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Diameter:

0.3750 inches

Shank Style:

Internally threaded w/bead

Overall Length:

1.7660 inches

Bore Diameter:

0.1900 inches

Overall Outside Diameter:

0.7810 inches

Lubrication Material:

Grease

Shank Thread Length:

0.8125 inches

Outer Ring Width:

0.3280 inches

Inner Ring Width:

0.4370 inches

Length From Bore Center To Shank End:

1.3750 inches

Shield Quantity:

2

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Width Across Flats:

0.4380 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Self-alignment Angle:

10.00 degrees

Special Features:

Shank end slotted 0.0620 in. W by 0.0560 in. Dp, no. 50 /0.0701 in./ hole in shank 0.3125 in. From end and at right angle to slot

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel shield or stainless steel shield

Surface Treatment:

Cadmium shield

Style Designator:

Double row, staggered, ball

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.