

View Online at <https://aerobasegroup.com/nsn/3110-00-277-0866>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.3440 inches

Overall Length:

0.8900 inches

Overall Outside Diameter:

Between 0.4995 inches and 0.5010 inches

Lubrication Material:

Grease

Stud Diameter:

Between 0.1890 inches and 0.1900 inches

Outer Ring Width:

Between 0.2805 inches and 0.2810 inches

Stud Length:

Between 0.5780 inches and 0.6250 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Special Features:

Ccotter pin hole in stud, with means for relubrication, thickness of chrome 0.0004 in. Min to 0.0007 in. Max, unthreaded portion of stud treated with currosion preventative mil-c-16173 or mil-c-11796

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp e52100

Material Specification:

66 federal standard single material response

Surface Treatment:

Cadmium exposed surfaces as mounted

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification 2nd treatment response exposed surfaces as mounted

Style Designator:

Cam follower

Thread Series Designator:

Unf

Specification Data:

80205-nas 562 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.