

View Online at <https://aerobasegroup.com/nsn/3110-00-364-7325>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Diameter:

0.3750 inches

Shank Style:

Internally threaded

Overall Length:

1.8580 inches

Bore Diameter:

Between 0.1895 inches and 0.1900 inches

Overall Outside Diameter:

0.8750 inches

Lubrication Material:

Grease

Shank Thread Length:

0.7500 inches

Outer Ring Width:

0.2500 inches

Inner Ring Width:

0.3750 inches

Length From Bore Center To Shank End:

1.4200 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Rigid

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel comp e52100 outer ring

Material Specification:

66 federal standard single material response outer ring

Surface Treatment:

Cadmium exposed surfaces as mounted

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response exposed surfaces as mounted

Style Designator:

Single row, ball

Test Data Document:

81349-mil-6866 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.