NSN 3110-00-400-5279

Cylindrical Roller Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3110-00-400-5279

Overall Width:
Between 0.6249 inches and 0.6299 inches
Bore Diameter:
Between 2.0680 inches and 2.0685 inches
Overall Outside Diameter:
Between 2.9523 inches and 2.9528 inches
Surface Finish:
Ground
Retainer Fabrication Method:
Machined
Locating Feature:
Nonlocating
Special Features:
Bearing stabilized for operation from m 65 to p 300 degrees f, 0.00008 in. Maximum variation in diameter of rollers
Material:
Steel roller
Material Specification:
Fed-std-66 federal standard single material response roller
Style Designator:
Single row, non-locating, two lip inner ring, cylindrical outer ring, separable
Test Data Document:
51600-es9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Or 38443-es105aa specification
(includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial
catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance
requirements and test conditions that are shown as "typical", "average", "", etc.). Or 38443-qc+2aaa specification (includes engineering
type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry
directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test
conditions that are shown as "typical", "average", "", etc.). Or 51600-es12aa specification (includes engineering type bulletins, brochures,
etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade
publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as
"typical", "average", "", etc.). Or 38443-es109aa specification (includes engineering type bulletins, brochures, etc., that reflect specification
type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type
data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Or
38443-qc+5aa specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a

No

Unit Of Measure:

Demilitarization: