

View Online at <https://aerobasegroup.com/nsn/3110-00-409-9849>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Diameter:**

Between 0.1800 inches and 0.1900 inches

**Shank Style:**

Externally threaded

**Overall Length:**

1.7655 inches

**Bore Diameter:**

Between 0.1897 inches and 0.1900 inches

**Overall Outside Diameter:**

0.7810 inches

**Lubrication Material:**

Grease

**Shank Thread Length:**

Between 0.7190 inches and 0.7810 inches

**Outer Ring Width:**

0.3280 inches

**Inner Ring Width:**

Between 0.4320 inches and 0.4370 inches

**Length From Bore Center To Shank End:**

1.3750 inches

**Seal Quantity:**

2

**Bearing Seal Type:**

Contact

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.190 inches

**Self-alignment Angle:**

10.00 degrees

**Special Features:**

Double row

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Steel comp 4130 inner ring race or steel comp 8620 inner ring race or steel comp e52100 inner ring race

**Material Specification:**

Mil-s-6758 military specification 1st material response inner ring race and mil-s-8690 military specification 2nd material response inner ring race and mil-s-7420 military specification 3rd material response inner ring race

**Surface Treatment:**

Cadmium all external/exposed metal surfaces

**Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response all external/exposed metal surfaces

**Style Designator:**

Double row, staggered, ball

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.