

View Online at <https://aerobasegroup.com/nsn/3110-00-505-3229>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.5890 inches and 0.6360 inches

Overall Length:

Between 1.8810 inches and 1.9330 inches

Overall Outside Diameter:

Between 0.9995 inches and 1.0010 inches

Lubrication Material:

Grease

Stud Diameter:

0.4370 inches

Outer Ring Width:

Between 0.5260 inches and 0.5310 inches

Stud Length:

Between 1.3550 inches and 1.4020 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.438 inches

Special Features:

Nas516-a lubrication fitting in stud end; keyway on stud end 0/8900 in. Min, 0.0930 in. Max. Wide by 0.0730 in. Min 0.0790 in. Maximum deep from end of stud to 0.7500 in. Min from washer face

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp 8620h stud

Surface Treatment:

Cadmium all external/exposed metal surfaces

Style Designator:

Cam follower

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.