

View Online at <https://aerobasegroup.com/nsn/3110-00-505-3229>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.5890 inches and 0.6360 inches

**Overall Length:**

Between 1.8810 inches and 1.9330 inches

**Overall Outside Diameter:**

Between 0.9995 inches and 1.0010 inches

**Lubrication Material:**

Grease

**Stud Diameter:**

0.4370 inches

**Outer Ring Width:**

Between 0.5260 inches and 0.5310 inches

**Stud Length:**

Between 1.3550 inches and 1.4020 inches

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.438 inches

**Special Features:**

Nas516-a lubrication fitting in stud end; keyway on stud end 0/8900 in. Min, 0.0930 in. Max. Wide by 0.0730 in. Min 0.0790 in. Maximum deep from end of stud to 0.7500 in. Min from washer face

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Steel comp 8620h stud

**Surface Treatment:**

Cadmium all external/exposed metal surfaces

**Style Designator:**

Cam follower

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.