

View Online at <https://aerobasegroup.com/nsn/3110-00-505-3240>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.6250 inches and 0.6720 inches

Overall Length:

Between 2.1560 inches and 2.2030 inches

Overall Outside Diameter:

Between 1.2495 inches and 1.2510 inches

Lubrication Material:

Grease

Stud Diameter:

0.5000 inches

Outer Ring Width:

Between 0.7450 inches and 0.7500 inches

Stud Length:

Between 1.4060 inches and 1.4530 inches

Thready Qty Per Inch (tpi):

20

Thread Size:

0.500 inches

Special Features:

Nas516-1 lubrication fitting in st, d end, keyway on stud end 0.8900 in. Min, 0.0930 in. Maximum wide by 0.0730 in. Min, 0.0790. Maximum deep from end of st, d to 0.7500 in. Min from washer face

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp 8620h stud

Surface Treatment:

Cadmium all external/exposed metal surfaces

Style Designator:

Cam follower

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.