

View Online at <https://aerobasegroup.com/nsn/3110-00-505-4237>

Shank Diameter:

Between 0.4430 inches and 0.4450 inches

Overall Length:

2.2910 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

Between 0.7500 inches and 0.8000 inches

Lubrication Material:

Grease

Outer Ring Width:

Between 0.3350 inches and 0.3500 inches

Inner Ring Width:

Between 0.4320 inches and 0.4370 inches

Length From Bore Center To Shank End:

Between 1.8760 inches and 1.9060 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Self-alignment Angle:

10.00 degrees

Special Features:

Solid shank unthreaded

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Stainless steel shield

Material Specification:

66 federal standard single material response outer ring

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.