

View Online at <https://aerobasegroup.com/nsn/3110-00-508-6969>

Shank Diameter:

Between 0.6230 inches and 0.6250 inches

Shank Style:

Hollow

Overall Length:

2.3600 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

Between 0.9200 inches and 0.9700 inches

Lubrication Material:

Grease

Outer Ring Width:

Between 0.3450 inches and 0.3600 inches

Inner Ring Width:

Between 0.5880 inches and 0.5930 inches

Length From Bore Center To Shank End:

Between 1.8600 inches and 1.8900 inches

Shank Bore Diameter:

0.3860 inches

Shank Bore Depth:

1.2850 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Self-alignment Angle:

15.00 degrees

Special Features:

With means for relubrication; unthreaded plain shank hollow

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel snap ring

Material Specification:

Aisi 4620 assn standard single material response rod end body

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.