

View Online at <https://aerobasegroup.com/nsn/3110-00-512-0903>

Bore Diameter:

Between 1.1809 inches and 1.1811 inches

Overall Outside Diameter:

Between 2.1651 inches and 2.1654 inches

Lubrication Material:

Petrolatum

Outer Ring Width:

Between 0.5108 inches and 0.5118 inches

Inner Ring Width:

Between 0.6249 inches and 0.6299 inches

Surface Finish:

Ground

Retainer Fabrication Method:

Machined

Load Direction:

Angular

Bore Shape:

Straight

Internal Clearance:

0.0014 inches radial and 0.0018 inches radial

Contact Angle:

18.5 degrees

Special Features:

Puller flange located on inner ring, 1.4750 in. Min, 1.4850 in. Maximum dia, 0.0300 in. Min, 0.0700 in. Maximum w, 0.0400 in. Min, 0.0600 maximum depth, split inner ring, stabilized for operation at 600 degrees f, c61.0 to c64.0 rockwell hardness rings and balls

Lubrication Material:

Lubricant

Lubrication Material Specification:

Mil-c-11796 military specification single material response

Material:

Steel separator

Material Specification:

Ams 6490 military standard single material response outer ring

Precious Material And Location:

Retainer silver

Precious Material:

Silver

Style Designator:

Non-loading groove, non-separable

Test Data Document:

73342-e1s1515 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 73342-e1s1003 specification

(includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-c-11796 spec.