

View Online at <https://aerobasegroup.com/nsn/3110-00-522-8969>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.3750 inches

Shank Style:

Externally threaded

Overall Length:

3.1400 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Overall Outside Diameter:

Between 1.3000 inches and 1.3500 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 1.2300 inches and 1.2600 inches

Outer Ring Width:

Between 0.3250 inches and 0.3400 inches

Inner Ring Width:

Between 0.4950 inches and 0.5000 inches

Length From Bore Center To Shank End:

Between 2.2350 inches and 2.2650 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Self-alignment Angle:

10.00 degrees

Special Features:

Radial internal clearance 0.0002 in. Min 0.0010 in. Max

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel snap ring

Material Specification:

Mil-s-7493 military specification single material response rod end body

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.