

View Online at <https://aerobasegroup.com/nsn/3110-00-591-7223>

Thread Class:

2a

Thread Direction:

Right-hand

Shank Diameter:

Between 0.1840 inches and 0.1900 inches

Shank Style:

Externally threaded

Overall Length:

1.1900 inches

Bore Diameter:

0.2500 inches

Overall Outside Diameter:

0.6600 inches

Lubrication Material:

Grease

Shank Thread Length:

0.4800 inches

Outer Ring Width:

0.4400 inches

Inner Ring Width:

0.4400 inches

Length From Bore Center To Shank End:

0.8600 inches

Alignment Type:

Rigid

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Special Features:

Cadmium plated pin 0.2500 in. Diameter by 0.9200 in. Lg through bore

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp e52100 roller

Material Specification:

Mil-s-5626 cond c4 federal specification single material response rod end body

Surface Treatment:

Cadmium

Style Designator:

Single row, needle roller

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.