

View Online at <https://aerobasegroup.com/nsn/3110-00-618-6649>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Diameter:**

0.6250 inches

**Shank Style:**

Externally threaded

**Overall Length:**

3.8600 inches

**Bore Diameter:**

0.3750 inches

**Overall Outside Diameter:**

1.6600 inches

**Lubrication Material:**

Grease

**Shank Thread Length:**

1.7500 inches

**Outer Ring Width:**

0.5500 inches

**Inner Ring Width:**

0.8120 inches

**Length From Bore Center To Shank End:**

3.0300 inches

**Seal Quantity:**

2

**Bearing Seal Type:**

Contact

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Thready Qty Per Inch (tpi):**

18

**Thread Size:**

0.625 inches

**Self-alignment Angle:**

10.00 degrees

**Special Features:**

Hcenterline of lower half of rod and eye is 0.0469 in. Lower than centerlineof bearing bore, two grease fittings, slot 0.0840 in. Deep by 0.1300 in. W by 1.7500 in. Long in shank, rod side of seal exposed

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Steel roller

**Surface Treatment:**

Cadmium all external/exposed metal surfaces

**Style Designator:**

Single row, concave rollers

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.