NSN 3110-00-624-3777

Needle Bearing Cam Follower - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-00-624-3777 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.3440 inches **Overall Length:** 1.0150 inches **Overall Outside Diameter:** Between 0.4995 inches and 0.5010 inches **Lubrication Material:** Grease Stud Diameter: Between 0.1900 inches and 0.1910 inches **Outer Ring Width:** Between 0.2805 inches and 0.2810 inches Stud Length: Between 0.7030 inches and 0.7500 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Special Features:** Heat treated stud, with cotter pin hole and 40 lubrication fitting, chrome thickness 0.0004 in. Min to 0.0007 in. Max, unthreaded portion of stud corrosion preventativemil-c-16173 or mil-c-11796 **Lubrication Material Specification:** Mil-g-23827 military specification single material response Material: Steel comp e52100 **Material Specification:** 66 federal standard single material response **Surface Treatment:** Cadmium all external/exposed metal surfaces **Style Designator:** Cam follower **Thread Series Designator:** Unf **Specification Data:** 80205-nas 562 professional/industrial association standard Shelf Life: N/a

--

Unit Of Measure:

NSN 3110-00-624-3777

Needle Bearing Cam Follower - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.