

View Online at <https://aerobasegroup.com/nsn/3110-00-628-4055>

**Thread Class:**

3a

**Thread Direction:**

Left-hand

**Shank Diameter:**

0.3750 inches

**Shank Style:**

Externally threaded

**Overall Length:**

2.3440 inches

**Bore Diameter:**

0.2500 inches

**Overall Outside Diameter:**

0.9380 inches

**Lubrication Material:**

Oil

**Shank Thread Length:**

1.1250 inches

**Outer Ring Width:**

0.4380 inches

**Inner Ring Width:**

0.5930 inches

**Length From Bore Center To Shank End:**

1.8750 inches

**Seal Quantity:**

2

**Bearing Seal Type:**

Contact

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Self-alignment Angle:**

10.00 degrees

**Special Features:**

Nas 513 keyway in shank, fill 80 pct min w/specified lubricant

**Lubrication Material Specification:**

Dc510, dow corning corporation mfr ref single material response

**Material:**

Steel comp e52100 inner ring

**Material Specification:**

Mil-s-7420 military specification single material response inner ring

**Surface Treatment:**

Cadmium all external/exposed metal surfaces

**Surface Treatment Specification:**

Qq-p-416, cl 2 federal specification single treatment response all external/exposed metal surfaces

**Style Designator:**

Double row, staggered, ball

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-s-6758 spec.