

View Online at <https://aerobasegroup.com/nsn/3110-00-633-4779>

Shank Diameter:

Between 0.2450 inches and 0.2500 inches

Shank Style:

Hollow

Overall Length:

3.0310 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

1.0620 inches

Lubrication Material:

Grease

Outer Ring Width:

Between 0.2190 inches and 0.2290 inches

Inner Ring Width:

Between 0.2760 inches and 0.2810 inches

Length From Bore Center To Shank End:

2.5000 inches

Shank Bore Diameter:

Between 0.1410 inches and 0.1460 inches

Shank Bore Depth:

Between 1.5150 inches and 1.5460 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Internal Clearance:

0.0000 inches radial and 0.0010 inches radial

Standard Tolerance Designation:

Afbma standard tolerance for rod end ball bearing

Special Features:

Plating on external surfaces of bearing only

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Stainless steel shield

Material Specification:

Mil-s-7720 military specification single material response rod end body

Surface Treatment:

Cadmium outer ring

Surface Treatment Specification:

Qq-p-416, type 1, class 2 federal specification single treatment response outer ring

Style Designator:

Single row, ball

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.