

View Online at <https://aerobasegroup.com/nsn/3110-00-679-6795>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

Between 0.2478 inches and 0.2483 inches

Shank Style:

Externally threaded

Overall Length:

2.7800 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

1.1250 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 0.4375 inches and 0.5000 inches

Outer Ring Width:

Between 0.3400 inches and 0.3500 inches

Inner Ring Width:

Between 0.4790 inches and 0.4840 inches

Length From Bore Center To Shank End:

2.2180 inches

Shield Quantity:

2

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel shield

Material Specification:

Mil-s-5626 military specification single material response rod end body

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Style Designator:

Single row, ball

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.