

View Online at <https://aerobasegroup.com/nsn/3110-00-702-5702>

Shank Diameter:

Between 0.6230 inches and 0.6250 inches

Shank Style:

Hollow

Overall Length:

Between 3.0425 inches and 3.0725 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Overall Outside Diameter:

Between 1.2350 inches and 1.2600 inches

Lubrication Material:

Grease

Outer Ring Width:

Between 0.6462 inches and 0.6662 inches

Inner Ring Width:

Between 0.8650 inches and 0.8700 inches

Length From Bore Center To Shank End:

Between 2.4275 inches and 2.4475 inches

Shank Bore Diameter:

Between 0.4900 inches and 0.5100 inches

Shank Bore Depth:

Between 1.5525 inches and 1.5725 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Self-alignment Angle:

Between 0.40 degrees and 0.60 degrees

Special Features:

Drilled hole filled w/hysol 6020 w/25 pct by weight hardener c

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel rod end body

Material Specification:

Sb4002-1, 78286 mfr ref single material response ball

Surface Treatment:

Cadmium all external/exposed metal surfaces

Style Designator:

Double row, staggered, ball

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.