

View Online at <https://aerobasegroup.com/nsn/3110-00-780-1809>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Shank Diameter:**

Between 0.3678 inches and 0.3750 inches

**Shank Style:**

Externally threaded

**Overall Length:**

3.0310 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Overall Outside Diameter:**

1.0620 inches

**Lubrication Material:**

Grease

**Shank Thread Length:**

1.2500 inches

**Outer Ring Width:**

Between 0.2190 inches and 0.2290 inches

**Inner Ring Width:**

Between 0.2760 inches and 0.2810 inches

**Length From Bore Center To Shank End:**

2.5000 inches

**Shield Quantity:**

2

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Stainless steel shield

**Material Specification:**

Mil-s-5626 military specification single material response rod end body

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response

**Style Designator:**

Single row, ball

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.