

View Online at <https://aerobasegroup.com/nsn/3110-00-803-0230>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.3750 inches

Shank Style:

Externally threaded

Overall Length:

2.3900 inches

Bore Diameter:

0.2500 inches

Overall Outside Diameter:

1.0200 inches

Lubrication Material:

Grease

Shank Thread Length:

1.0600 inches

Outer Ring Width:

0.3600 inches

Inner Ring Width:

0.5930 inches

Length From Bore Center To Shank End:

1.8800 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Self-alignment Angle:

10.00 degrees

Special Features:

Keyway in shank 1.1500 in. Lg 0.093 in. Min 0.098 in. Maximum 0.064 in. Min 0.069 in. Maximum deep, flush type grease fitting, radial clearance 0.0000 in. To 0.0006 in.

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp 4620 rod end body

Material Specification:

Qq-s-763 federal specification single material response shield

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.