

View Online at <https://aerobasegroup.com/nsn/3110-00-805-0162>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

1.0000 inches

Shank Style:

Externally threaded

Overall Length:

6.0000 inches

Bore Diameter:

0.6250 inches

Overall Outside Diameter:

2.8000 inches

Lubrication Material:

Grease

Shank Thread Length:

2.5600 inches

Outer Ring Width:

0.8500 inches

Inner Ring Width:

1.2500 inches

Length From Bore Center To Shank End:

4.6600 inches

Shield Quantity:

2

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

14

Thread Size:

1.000 inches

Self-alignment Angle:

10.00 degrees

Special Features:

2 seal washers, keyway in shank to accept nas51316 lockwasher

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel roller

Surface Treatment:

Cadmium all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.