## NSN 3110-00-806-2428

**Thread Class:** 

Right-hand

**Thread Direction:** 

3b

Rod End Roller Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-00-806-2428

Shank Diameter:
Between 0.6180 inches and 0.6200 inches
Shank Style:
653 internally threaded
Overall Length:
Between 2.3300 inches and 2.3700 inches
Bore Diameter:
Between 0.2495 inches and 0.2500 inches
Overall Outside Diameter:
Between 0.9350 inches and 0.9700 inches
Lubrication Material:
Grease
Shank Thread Length:
Between 1.0938 inches and 1.1562 inches
Outer Ring Width:
0.3594 inches
Inner Ring Width:
Between 0.5880 inches and 0.5930 inches
Length From Bore Center To Shank End:
1.8750 inches
Shield Quantity:
2
Alignment Type:
Self-aligning
Self-alignment Location:
Internal
Thready Qty Per Inch (tpi):
20
Thread Size:
0.438 inches
Self-alignment Angle:
Between 0.35 degrees and 0.65 degrees
Lubrication Material Specification:
Mil-g-23827 military specification single material response
Material:
Stainless steel rod end body
Material Specification:
Fed-std-66 federal standard single material response roller

## NSN 3110-00-806-2428

Rod End Roller Bearing - Page 2 of 2



Style Designator:
Single row, concave rollers
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A044a0

Mil-std (military Standard):

Mil-g-23827 spec.