

View Online at <https://aerobasegroup.com/nsn/3110-00-806-2428>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Diameter:**

Between 0.6180 inches and 0.6200 inches

**Shank Style:**

653 internally threaded

**Overall Length:**

Between 2.3300 inches and 2.3700 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Overall Outside Diameter:**

Between 0.9350 inches and 0.9700 inches

**Lubrication Material:**

Grease

**Shank Thread Length:**

Between 1.0938 inches and 1.1562 inches

**Outer Ring Width:**

0.3594 inches

**Inner Ring Width:**

Between 0.5880 inches and 0.5930 inches

**Length From Bore Center To Shank End:**

1.8750 inches

**Shield Quantity:**

2

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.438 inches

**Self-alignment Angle:**

Between 0.35 degrees and 0.65 degrees

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Stainless steel rod end body

**Material Specification:**

Fed-std-66 federal standard single material response roller

**Style Designator:**

Single row, concave rollers

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.