

View Online at <https://aerobasegroup.com/nsn/3110-00-865-8962>

**Bore Diameter:**

Between 0.1860 inches and 0.1875 inches

**Lubrication Material:**

Oil

**Flange Outside Diameter:**

Between 0.4210 inches and 0.4220 inches

**Flange Width:**

Between 0.0300 inches and 0.0310 inches

**Outer Ring Width:**

Between 0.1240 inches and 0.1250 inches

**Inner Ring Width:**

Between 0.1552 inches and 0.1562 inches

**Outer Ring Outside Diameter:**

Between 0.3748 inches and 0.3750 inches

**Surface Finish:**

Ground

**Retainer Fabrication Method:**

Pressed

**Shield Quantity:**

2

**Load Direction:**

Radial

**Bore Shape:**

Straight

**Internal Fit-up Designation:**

Tight

**Internal Clearance:**

0.0002 inches radial and 0.0005 inches radial

**Standard Tolerance Designation:**

Abec no.7

**Lubrication Material Specification:**

Mil-I-6085 military specification single material response

**Material:**

Stainless steel shield

**Style Designator:**

Non-loading groove, non-separable

**Reference Number Differentiating Characteristics:**

Fleet ballistic missile quality, as identified by qualitycontrol no. Poso401189

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A044a0

**Mil-std (military Standard):**

Mil-I-6085 spec.