

View Online at <https://aerobasegroup.com/nsn/3110-00-865-8962>

Bore Diameter:

Between 0.1860 inches and 0.1875 inches

Lubrication Material:

Oil

Flange Outside Diameter:

Between 0.4210 inches and 0.4220 inches

Flange Width:

Between 0.0300 inches and 0.0310 inches

Outer Ring Width:

Between 0.1240 inches and 0.1250 inches

Inner Ring Width:

Between 0.1552 inches and 0.1562 inches

Outer Ring Outside Diameter:

Between 0.3748 inches and 0.3750 inches

Surface Finish:

Ground

Retainer Fabrication Method:

Pressed

Shield Quantity:

2

Load Direction:

Radial

Bore Shape:

Straight

Internal Fit-up Designation:

Tight

Internal Clearance:

0.0002 inches radial and 0.0005 inches radial

Standard Tolerance Designation:

Abec no.7

Lubrication Material Specification:

Mil-I-6085 military specification single material response

Material:

Stainless steel shield

Style Designator:

Non-loading groove, non-separable

Reference Number Differentiating Characteristics:

Fleet ballistic missile quality, as identified by qualitycontrol no. Poso401189

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-I-6085 spec.