

View Online at <https://aerobasegroup.com/nsn/3110-00-902-9318>

Bore Diameter:

Between 0.2500 inches and 0.2503 inches

Lubrication Material:

Grease

Flange Outside Diameter:

0.6870 inches

End Application:

Supply class aoe; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); spruance class dd (963); seawolf class ssn; ticonderoga class cg (47); oliver perry class ffg; sturgeon class ssn (637); los angeles class ssn (688); austin ship class lpd-4 amphibious transport docks; fms - knox class ff

Flange Width:

0.0420 inches

Outer Ring Width:

0.2260 inches

Inner Ring Width:

0.2500 inches

Outer Ring Outside Diameter:

Between 0.6253 inches and 0.6257 inches

Surface Finish:

Ground

Retainer Fabrication Method:

Pressed

Shield Quantity:

2

Load Direction:

Radial

Bore Shape:

Straight

Internal Clearance:

0.0002 inches radial and 0.0005 inches radial

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Stainless steel

Style Designator:

Non-loading groove, non-separable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.