NSN 3110-00-911-3834 Needle Bearing Cam Follower - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/3110-00-911-3834 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.3750 inches |
| Overall Length: |
| 1.4062 inches |
| Overall Outside Diameter: |
| 0.8135 inches |
| Lubrication Material: |
| Grease |
| Stud Diameter: |
| 0.3750 inches |
| Outer Ring Width: |
| 0.4000 inches |
| Stud Length: |
| 0.8750 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.375 inches |
| Special Features: |
| Nas 516 grease fitting located in bearing end, 2.000 in radius on od |
| Lubrication Material Specification: |
| Mil-g-23827 military specification single material response |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium all external/exposed metal surfaces |
| Style Designator: |
| Cam follower |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A044a0

NSN 3110-00-911-3834

Needle Bearing Cam Follower - Page 2 of 2



Mil-std (military Standard):

Mil-g-23827 spec.