NSN 3110-00-915-3278

Rod End Ball Bearing - Page 1 of 2

Thread Class:



| 3a |
|---|
| Thread Direction: |
| Left-hand |
| Shank Diameter: |
| 0.3750 inches |
| Shank Style: |
| Externally threaded |
| Overall Length: |
| 2.3440 inches |
| Bore Diameter: |
| 0.2500 inches |
| Lubrication Material: |
| Grease |
| Outer Ring Width: |
| 0.4380 inches |
| Inner Ring Width: |
| 0.5930 inches |
| Length From Bore Center To Shank End: |
| 1.8750 inches |
| Retainer Fabrication Method: |
| Pressed |
| Seal Quantity: |
| 2 |
| Bearing Seal Type: |
| Contact |
| Alignment Type: |
| Self-aligning |
| Self-alignment Location: |
| Internal |
| Internal Clearance: |
| 0.0000 inches radial and 0.0004 inches radial |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.375 inches |
| Standard Tolerance Designation: |
| Afbma standard tolerance for rod end ball bearing |
| Self-alignment Angle: |
| 10.00 degrees |

Lubrication Material Specification:Mil-g-23827 military specification single material response

NSN 3110-00-915-3278

Rod End Ball Bearing - Page 2 of 2



| Material: |
|--|
| Steel comp e52100 inner ring |
| Material Specification: |
| Aisi assn standard single material response retainer |
| Surface Treatment: |
| Cadmium |
| Style Designator: |
| Double row, staggered, ball |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A044a0 |

Mil-std (military Standard):

Mil-g-23827 spec.