

View Online at <https://aerobasegroup.com/nsn/3110-00-928-2343>

**Overall Width:**

Between 0.1774 inches and 0.1874 inches

**Bore Diameter:**

0.1250 inches

**Overall Outside Diameter:**

0.2500 inches

**Lubrication Material:**

Lubricating oil

**Calibration Designator:**

C

**Surface Finish:**

Ground

**Retainer Fabrication Method:**

Pressed

**Shield Quantity:**

2

**Load Direction:**

Angular

**Standard Tolerance Designation:**

Abec no.7

**Bearing Preload Rating:**

Between 0.5 pounds and 1.5 pounds

**Contact Angle:**

Between 14.0 degrees and 19.0 degrees

**Special Features:**

Pair of bearings, duplex mounted unshielded sides. Maximum torque 20.000 mg/mm under 75 gm thrust load w/lubricating oil applied. V mark on of bearing assembly

**Lubrication Material Specification:**

Mil-I-6085 military specification single material response

**Material:**

Stainless steel

**Style Designator:**

92b counterbored outer rings, non-separable, back to back mounting

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-I-6085 spec.