

View Online at <https://aerobasegroup.com/nsn/3110-00-930-2588>

Shank Diameter:

Between 0.3540 inches and 0.3590 inches

Shank Style:

Hollow

Overall Length:

7.4380 inches

Bore Diameter:

Between 0.3120 inches and 0.3125 inches

Overall Outside Diameter:

1.5000 inches

Lubrication Material:

Grease

Outer Ring Width:

Between 0.3750 inches and 0.3850 inches

Inner Ring Width:

Between 0.5530 inches and 0.5580 inches

Length From Bore Center To Shank End:

6.6880 inches

Shank Bore Diameter:

Between 0.2030 inches and 0.2080 inches

Shank Bore Depth:

Between 2.2500 inches and 2.2810 inches

Shield Quantity:

2

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Self-alignment Angle:

10.00 degrees

Special Features:

Single row of balls

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Stainless steel shield

Material Specification:

Mil-s-7720 military specification single material response rod end body

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

Style Designator:

Double row, staggered, ball

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.