NSN 3110-00-930-2588

Rod End Ball Bearing - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3110-00-930-2588

Shank Diameter:
Between 0.3540 inches and 0.3590 inches
Shank Style:
Hollow
Overall Length:
7.4380 inches
Bore Diameter:
Between 0.3120 inches and 0.3125 inches
Overall Outside Diameter:
1.5000 inches
Lubrication Material:
Grease
Outer Ring Width:
Between 0.3750 inches and 0.3850 inches
Inner Ring Width:
Between 0.5530 inches and 0.5580 inches
Length From Bore Center To Shank End:
6.6880 inches
Shank Bore Diameter:
Between 0.2030 inches and 0.2080 inches
Shank Bore Depth:
Between 2.2500 inches and 2.2810 inches
Shield Quantity:
2
Alignment Type:
Self-aligning
Self-alignment Location:
Internal
Self-alignment Angle:
10.00 degrees
Special Features:
Single row of balls
Lubrication Material Specification:
Mil-g-23827 military specification single material response
Material:
Stainless steel shield
Material Specification:
Mil-s-7720 military specification single material response rod end body
Surface Treatment:
Cadmium
Surface Treatment Specification:

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response

NSN 3110-00-930-2588

Rod End Ball Bearing - Page 2 of 2



Style Designator:			
Double row,	staggered,	ball	

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.