

View Online at <https://aerobasegroup.com/nsn/3110-00-945-0465>

**Bore Diameter:**

Between 2.7553 inches and 2.7557 inches

**Overall Outside Diameter:**

Between 4.3305 inches and 4.3309 inches

**Outer Ring Width:**

Between 0.6987 inches and 0.7087 inches

**Inner Ring Width:**

Between 0.8550 inches and 0.8650 inches

**Surface Finish:**

Ground

**Retainer Fabrication Method:**

Molded

**Load Direction:**

Radial

**Bore Shape:**

Straight

**Internal Clearance:**

0.0004 inches radial

**Special Features:**

Stabilized for operation at m 65 degrees f to p 250 f; os ns is xoppwe plated per ams2418 0.0001 in. Max; serial no. Marked on od; etch v and 6 on od of outer race at point of maximum radial runout

**Material Specification:**

Ams 6440 assn standard single material response outer ring or ams 6441 assn standard single material response outer ring

**Style Designator:**

26c counterbored outer ring, non-separable

**Test Data Document:**

81343-ams2640 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A044a0