NSN 3110-00-947-3543

Cylindrical Roller Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3110-00-947-3543

Overall Width: 16.00 millimeters **Bore Diameter:** 30.00 millimeters **Overall Outside Diameter:** 62.00 millimeters Surface Finish: Ground **Retainer Fabrication Method:** Machined **Bore Shape:** Straight **Locating Feature:** Two direction **Internal Clearance:** 0.0007 inches radial and 0.0024 inches radial **Standard Tolerance Designation:** Rbec no.5 **Special Features:** Stabilized for operation at 250 degrees f max, bearing components marked w/same ser no., 2 slots on inner ring on side plate side 180 degrees apart, 0.029-0.033 in. Deep, 0.057-0.067 in. W Material: Steel side plate **Material Specification:** Ams 6440 assn standard single material response roller Style Designator: 250a single row, non-locating, two lip inner ring, cylindrical outer ring with two roller retainment rings on outer, non-separable **Test Data Document:** 73342-eis10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 73342-eis11a69 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 73342-eis15a22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 73342-eis10a17 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 73342-eis15a10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life: