NSN 3110-00-949-7986

Unit Of Measure:

Domilitarization

Cylindrical Roller Bearing - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3110-00-949-7986

Overall Width:
21.00 millimeters
Bore Diameter:
35.00 millimeters
Overall Outside Diameter:
80.00 millimeters
Surface Finish:
Ground
Retainer Fabrication Method:
Machined
Bore Shape:
Straight
Locating Feature:
One direction
Internal Clearance:
0.0012 inches radial and 0.0017 inches radial
Standard Tolerance Designation:
Rbec no.5
Special Features:
Inner and outer ring raceways to be straight within 0.0001 in. Tir, stabilized for operation at m65 degrees f to p400 degrees f, rockwell
hardness rating of rollers, inner and outer rings 58.0 to 61.0 c scale, retainer 55.0 to 75.0 b scale, inner and outer ring raceways 6 uin aa,
rollers 2 to 5 uin aa, inner ring bore surface 20 uin aa, outer ring od surface 15 uin aa, outer ring lips and retainer od surface 32 uin aa, cage
pockets 64 uin aa
Material:
Steel roller
Material Specification:
1-300-031, 91547 mfr ref single material response roller
Precious Material And Location:
Retainer silver
Precious Material:
Silver
Style Designator:
252f single row, one-direction locating, one lip inner ring, two lip outer ring, separable
Test Data Document:
E1004-91547 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And +6903-91547 specification (includes
engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs,
industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and
test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a