

View Online at <https://aerobasegroup.com/nsn/3110-00-966-9734>

Bore Diameter:

Between 0.1875 inches and 0.1877 inches

Lubrication Material:

Grease

Flange Outside Diameter:

Between 0.6230 inches and 0.6300 inches

Flange Width:

Between 0.0400 inches and 0.0440 inches

Outer Ring Width:

Between 0.2220 inches and 0.2260 inches

Inner Ring Width:

Between 0.2490 inches and 0.2510 inches

Calibration Designator:

C

Surface Finish:

Ground

Retainer Fabrication Method:

Pressed

Shield Quantity:

2

Load Direction:

Radial

Bore Shape:

Straight

Internal Fit-up Designation:

Standard

Internal Clearance:

0.0002 inches radial and 0.0003 inches radial

Standard Tolerance Designation:

Abec no.5

Outer Ring Taper:

0.0800 per foot in inches

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Stainless steel shield

Material Specification:

66 federal standard single material response outer ring

Style Designator:

Non-loading groove, non-separable

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.