

View Online at <https://aerobasegroup.com/nsn/3110-00-966-9734>

**Bore Diameter:**

Between 0.1875 inches and 0.1877 inches

**Lubrication Material:**

Grease

**Flange Outside Diameter:**

Between 0.6230 inches and 0.6300 inches

**Flange Width:**

Between 0.0400 inches and 0.0440 inches

**Outer Ring Width:**

Between 0.2220 inches and 0.2260 inches

**Inner Ring Width:**

Between 0.2490 inches and 0.2510 inches

**Calibration Designator:**

C

**Surface Finish:**

Ground

**Retainer Fabrication Method:**

Pressed

**Shield Quantity:**

2

**Load Direction:**

Radial

**Bore Shape:**

Straight

**Internal Fit-up Designation:**

Standard

**Internal Clearance:**

0.0002 inches radial and 0.0003 inches radial

**Standard Tolerance Designation:**

Abec no.5

**Outer Ring Taper:**

0.0800 per foot in inches

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Stainless steel shield

**Material Specification:**

66 federal standard single material response outer ring

**Style Designator:**

Non-loading groove, non-separable

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.