

View Online at <https://aerobasegroup.com/nsn/3110-00-971-6338>

**Overall Width:**

Between 1.7430 inches and 1.7460 inches

**Bore Diameter:**

Between 0.7495 inches and 0.7500 inches

**Smallest Outside Diameter:**

Between 1.1241 inches and 1.1246 inches

**Surface Finish:**

Ground

**Bore Shape:**

Straight

**Special Features:**

Outside lip service and lip od surface cadmium-plated per qq-p-416, class 3, type 2, c60.0 to c65.0 rockwell hardness, od surface fin. 16 uin aa, lip od, lip inside and outside, id 32 uin aa, inside and outside surface of lip parallel within 0.001 in., left end surface of body and lip parallel to right end surface of body within 0.001 in., id and od conc within 0.002 in. Tir, od and inside surface of lip sq within 0.001 in.

**Material:**

Steel

**Material Specification:**

Mil-s-7430 cond e2 military specification single material response

**Style Designator:**

Inner ring, roller, single lip

**Test Data Document:**

97499-abpsfa w4075 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 97499-abpsfaaw4092 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-s-7430 spec.