NSN 3110-00-973-8282

Rod End Ball Bearing - Page 1 of 2

Shank Diameter:



View Online at https://aerobasegroup.com/nsn/3110-00-973-8282

| Between 0.4340 inches and 0.4360 inches |
|--|
| Shank Style: |
| Solid |
| Overall Length: |
| 2.7810 inches |
| Bore Diameter: |
| Between 0.2495 inches and 0.2500 inches |
| Overall Outside Diameter: |
| 1.0620 inches |
| Lubrication Material: |
| Grease |
| Outer Ring Width: |
| Between 0.2190 inches and 0.2290 inches |
| Inner Ring Width: |
| Between 0.2760 inches and 0.2810 inches |
| Length From Bore Center To Shank End: |
| 2.2500 inches |
| Shield Quantity: |
| 2 |
| Alignment Type: |
| Self-aligning |
| Self-alignment Location: |
| Internal |
| Self-alignment Angle: |
| 8.00 degrees |
| Special Features: |
| Single row of balls |
| Lubrication Material Specification: |
| Mil-g-23827 military specification single material response |
| Material: |
| Stainless steel shield |
| Material Specification: |
| Qq-a-200/2 federal specification single material response rod end body |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 1, cl 2 federal specification single treatment response |
| Style Designator: |
| Double row, staggered, ball |
| Shelf Life: |
| N/a |

NSN 3110-00-973-8282

Rod End Ball Bearing - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

Yes - demil/mli

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.