

View Online at <https://aerobasegroup.com/nsn/3110-00-977-8704>

Bore Diameter:

Between 0.2498 inches and 0.2500 inches

Overall Outside Diameter:

Between 0.9009 inches and 0.9014 inches

Lubrication Material:

Grease

Outer Ring Width:

0.4640 inches

Inner Ring Width:

Between 0.6820 inches and 0.6870 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Load Direction:

Radial

Self-alignment Location:

Internal

Special Features:

10 degrees self-alignment in either direction; radial clearance 0.0004 in. Max; controlled starting and alignment torque; lube with 0.24 min to 0.30 maximum gms of specified grease; seals to be sandwich type 1c steel with polytetrafluoroethylene seal ring; rings heat stabilized at 300 degrees f and 0.4640 in. Maximum to 0.4590 in. Maximum with outer ring tolerance

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel outer ring

Surface Treatment:

Cadmium all external/exposed metal surfaces

Style Designator:

Double row, self aligning

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.