

View Online at <https://aerobasegroup.com/nsn/3110-01-011-3600>

**Thread Class:**

3b

**Thread Direction:**

Right-hand

**Shank Diameter:**

0.4370 inches

**Shank Style:**

653 internally threaded

**Overall Length:**

Between 1.7650 inches and 1.7700 inches

**Bore Diameter:**

Between 0.2495 inches and 0.2500 inches

**Overall Outside Diameter:**

Between 0.7500 inches and 0.8000 inches

**Lubrication Material:**

Grease

**Shank Thread Length:**

Between 0.7500 inches and 0.8100 inches

**Outer Ring Width:**

Between 0.3350 inches and 0.3500 inches

**Inner Ring Width:**

Between 0.4320 inches and 0.4370 inches

**Length From Bore Center To Shank End:**

Between 1.3650 inches and 1.3950 inches

**Seal Quantity:**

2

**Shield Quantity:**

2

**Bearing Seal Type:**

Contact

**Alignment Type:**

Self-aligning

**Self-alignment Location:**

Internal

**Width Across Flats:**

0.4370 inches

**Special Features:**

Keyway in shank, grease fitting in head

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Surface Treatment:**

Cadmium all external/exposed metal surfaces

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

**Style Designator:**

Single row, concave rollers

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.