

View Online at <https://aerobasegroup.com/nsn/3110-01-019-2660>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.2500 inches

Shank Style:

Externally threaded

Overall Length:

Between 2.6400 inches and 2.6600 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

Between 0.7500 inches and 0.8000 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 1.2600 inches and 1.3200 inches

Outer Ring Width:

Between 0.3350 inches and 0.3500 inches

Inner Ring Width:

Between 0.4320 inches and 0.4370 inches

Length From Bore Center To Shank End:

Between 1.8600 inches and 1.8900 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Special Features:

Grease fitting in head, nas 559 keyway in shank

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.