

View Online at <https://aerobasegroup.com/nsn/3110-01-022-2042>

Thread Class:

3b

Thread Direction:

Right-hand

Shank Diameter:

Between 0.6100 inches and 0.6200 inches

Shank Style:

653 internally threaded

Overall Length:

2.3600 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

0.9700 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 1.0940 inches and 1.1540 inches

Outer Ring Width:

Between 0.3450 inches and 0.3600 inches

Inner Ring Width:

Between 0.5880 inches and 0.5930 inches

Length From Bore Center To Shank End:

Between 1.8600 inches and 1.8750 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

20

Thread Size:

0.438 inches

Self-alignment Angle:

15.00 degrees

Special Features:

Slot across face of shank end 0.0950 in. W 0.0720 in. Deep

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel comp e3310 rod end body

Material Specification:

Qq-s-763 federal specification single material response shield

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.