

View Online at <https://aerobasegroup.com/nsn/3110-01-025-0853>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.2500 inches

Shank Style:

651 externally threaded

Overall Length:

Between 2.2650 inches and 2.2700 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

Between 0.7500 inches and 0.8000 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 1.2500 inches and 1.3100 inches

Outer Ring Width:

Between 0.3350 inches and 0.3500 inches

Inner Ring Width:

Between 0.4320 inches and 0.4370 inches

Length From Bore Center To Shank End:

Between 1.8650 inches and 1.8950 inches

Seal Quantity:

2

Shield Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Self-alignment Angle:

10.00 degrees

Special Features:

0.0002 in. Min 0.0010 in. Maximum radial internal clearance, plastic flush type grease fitting located 45 degrees by 0.4840 in. Maximum from center line

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel snap ring

Material Specification:

Qq-s-763 federal specification single material response shield

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Single row, concave rollers

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.