

View Online at <https://aerobasegroup.com/nsn/3110-01-025-4455>

Thread Class:

3a

Thread Direction:

Left-hand

Shank Diameter:

0.3750 inches

Shank Style:

Externally threaded

Overall Length:

1.7655 inches

Bore Diameter:

Between 0.1897 inches and 0.1900 inches

Overall Outside Diameter:

Between 0.7710 inches and 0.7910 inches

Lubrication Material:

Grease

Shank Thread Length:

Between 0.7190 inches and 0.7810 inches

Outer Ring Width:

Between 0.3180 inches and 0.3380 inches

Inner Ring Width:

Between 0.4320 inches and 0.4370 inches

Length From Bore Center To Shank End:

Between 1.3650 inches and 1.3850 inches

Retainer Fabrication Method:

Pressed

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

External

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Self-alignment Angle:

10.00 degrees

Special Features:

80 pct of specified lubrication

Lubrication Material Specification:

Mil-g-81322 military specification single material response

Material:

Steel comp e52100 inner race

Material Specification:

Mil-s-7420 military specification single material response inner race

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 1, cl 2 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Double row, staggered, ball

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A044a0

Mil-std (military Standard):

Mil-g-81322 spec.