

View Online at <https://aerobasegroup.com/nsn/3110-01-036-3057>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.5310 inches and 0.5930 inches

**Overall Length:**

Between 1.1890 inches and 1.2760 inches

**Overall Outside Diameter:**

Between 0.8740 inches and 0.8760 inches

**Lubrication Material:**

Grease

**Stud Diameter:**

Between 0.3740 inches and 0.3760 inches

**Outer Ring Width:**

Between 0.4640 inches and 0.4690 inches

**Stud Length:**

Between 0.7250 inches and 0.8070 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Special Features:**

Nas516 lubricator in roller end, cotter pin hole 0.106 in. Diameter located 0.156 in. From end of stud

**Lubrication Material Specification:**

Mil-g-23827 military specification single material response

**Material:**

Steel comp e52100 stud or steel comp 8620 stud or steel comp 8720 stud or steel comp 4620 stud or steel comp 8620h stud

**Material Specification:**

Mil-s-7420 military specification single material response outer ring

**Surface Treatment:**

Cadmium end plate

**Surface Treatment Specification:**

Qq-p-416, type 1, cl 2 federal specification single treatment response stud

**Style Designator:**

Cam follower

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A044a0

**Mil-std (military Standard):**

Mil-g-23827 spec.