

View Online at <https://aerobasegroup.com/nsn/3110-01-040-4843>

Thread Class:

3a

Thread Direction:

Right-hand

Shank Diameter:

0.3125 inches

Shank Style:

Externally threaded

Overall Length:

1.6910 inches

Bore Diameter:

Between 0.1895 inches and 0.1900 inches

Overall Outside Diameter:

0.7810 inches

Lubrication Material:

Grease

Shank Thread Length:

0.7400 inches

Outer Ring Width:

0.4380 inches

Inner Ring Width:

0.5620 inches

Length From Bore Center To Shank End:

1.3000 inches

Seal Quantity:

2

Bearing Seal Type:

Contact

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Thready Qty Per Inch (tpi):

24

Thread Size:

0.312 inches

Self-alignment Angle:

10.00 degrees

Special Features:

Nas513 keyway in shank

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel rod end body

Surface Treatment:

Cadmium all external/exposed metal surfaces

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response all external/exposed metal surfaces

Style Designator:

Double row, staggered, ball

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.