

View Online at <https://aerobasegroup.com/nsn/3110-01-055-3945>

Shank Diameter:

Between 0.6230 inches and 0.6250 inches

Shank Style:

Hollow

Overall Length:

2.0930 inches

Bore Diameter:

Between 0.2495 inches and 0.2500 inches

Overall Outside Diameter:

Between 0.9280 inches and 0.9480 inches

Lubrication Material:

Grease

Outer Ring Width:

Between 0.4280 inches and 0.4480 inches

Inner Ring Width:

Between 0.5880 inches and 0.5930 inches

Length From Bore Center To Shank End:

Between 1.6150 inches and 1.6350 inches

Shank Bore Diameter:

Between 0.5156 inches and 0.5163 inches

Shank Bore Depth:

0.8750 inches

Shield Quantity:

2

Alignment Type:

Self-aligning

Self-alignment Location:

Internal

Self-alignment Angle:

10.00 degrees

Special Features:

Rivet hole 0.1250 in. Min diameter located 0.5000 in. From end of shank

Lubrication Material Specification:

Mil-g-23827 military specification single material response

Material:

Steel rod end body

Surface Treatment:

Cadmium all external/exposed metal surfaces

Style Designator:

Double row, staggered, ball

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A044a0

Mil-std (military Standard):

Mil-g-23827 spec.